



莘茂複合材料股份有限公司

EPOTECH COMPOSITE CORPORATION

TEL: 886-4-24630896

FAX: 886-4-24630806

Email e-service@epotechcorp.com

TUPH™ - Z RESIN

TUPH™ - Z resin is epoxy resin functionalised with polyester type polyols to form pre-formed Inter Penetration Networks which is designed for outer pressure moulding processes of fibre composites. These pre-formed IPN network will be chemical bonded following up the desired curing pattern with epoxy resins under flow controlled as well as fibre-washing prevention. High hydroxyl groups provides good adhesion to fibres.

PACKAGE

1. 5 gallon barrel.
2. Z: 20kg/barrel; Z(60): 18kg/barrel.

■ HANDLING AND STORAGE

STORAGE TEMPERATURE: At room temperature. Store in a cool, dry well-ventilated location and stay away from excessive heat and flames.

HANDLING: Wear protective mask /glasses/gloves/clothing. Wash thoroughly after handling.

■ IMPORTANT

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Epotech Composite Corporation. The data on this sheet is related only to the specific material designated herein. All statement, technical information and recommendation in this data sheet are given in good faith and based on tests believed to be reliable; but their accuracy and completeness are not guaranteed. They do not constitute an offer to any person and shall not be deemed to form the basis of any subsequent contract, nor to constitute any warranty or representation as to quality, merchantability or fitness for purpose.

